



CHARACTERISTICS

- EUROBAT specification long life
- Absorbent Glass Mat (AGM) technology
- Extremely high cycle life and float life performance
- Wide range of operating temperature -20°C to +50°C
- Delivered ready for use at 100% of its nominal capacity
- Easy for installation, maintenance free operation
- Shock resistant ABS flame retardant container and lid
- UL, CE, ISO9001 recognized component
- Non-hazardous cargo for ground
- Calcium tin alloy grid for high power density

CODE	Nominal Voltage (V)	Capacity (AH)	Length	Width	Height	Kg	Terminal
WKE127	12	7	151	65	94	2.15	T1
WKE1220	12	20	180	77	167	5.80	T8
5 years Warranty							
WKE1240	12	40	197	165	170	13.00	T4
WKE1265	12	65	350	167	179	22.00	T9
WKE1280	12	80	350	167	179	24.00	T9
WKE12100	12	100	330	171	214	30.00	T9
WKE12120	12	120	409	176	225	33.00	T11
WKE12150	12	150	485	172	240	42.00	T11
WKE12180	12	180	494	206	209	55.00	T11
WKE12200	12	200	522	238	218	58.00	T11
WKE12250	12	250	521	269	220	68.00	T11
10 Years Warranty							
WKE12100 GEL	12	100	330	171	214	31.00	T9
WKE12150 GEL	12	150	485	172	240	45.50	T11
WKE12200 GEL	12	200	522	238	218	64.00	T11
WKE12250 GEL	12	250	521	269	220	78.00	T11
12 years Warranty							

OTHER POWERS ON REQUEST